



Project _____

Item No. _____

Quantity _____




THE C3



PERFORMANCE

- The C3 roasts, browns and broils a wide variety of foods up to 10X faster, at a quality that meets or exceeds traditional cooking methods



1. Blower Motor
2. Impinged Air
3. Microwave Bursts
4. Impingement Heater
5. Catalytic Converter

EXTERIOR CONSTRUCTION

- 430 stainless steel front, top, sides and back
- 4" (102 mm) adjustable legs
- Powder coated handle
- Cool to the touch pull down door with microwave seal

INTERIOR CONSTRUCTION

- Fully insulated and sealed cook chamber
- 304 stainless steel liner with large radius corners
- 304 stainless steel removable grease collection pan

STANDARD FEATURES

- Integral recirculating catalytic converter system for UL listed ventless operation (UL KNLZ)
- Variable-speed High h recirculating impingement airflow system
- Bottom-launched microwave system
- Smart menu system capable of storing up to 128 recipes
- Built-in self-diagnostics for monitoring oven components and performance
- Stackable design (requires stacking kit)
- Includes plug and cord (5 ft.)
- Ceramic cooking platter
- Warranty – one year parts and labor






This product conforms to the ventilation recommendations set forth by NFPA96 using EPA202 test method.

If you have questions regarding ventless certifications or local codes please email ventless.help@turbochef.com

TurboChef Global Operations

4240 International Pkwy, Suite 105
 Carrollton, Texas 75007 USA
 US: 800.90TURBO (800.908.8726)
 International: +1 214.379.6000
 Fax: +1 214.379.6073
turbochef.com

TC3-0324/Revision C/
January 2007



DIMENSIONS		
Single Units		
Height	21.5"	(546 mm)
on legs	25.5"	(648 mm)
Width	29"	(737 mm)
Depth	29.5"	(749 mm)
with handle	32.25"	(819 mm)
Weight	255 lbs.	(116 kg)
Stacked Units (Stacking Kit Required)		
Height	43"	(1092 mm)
Width	29"	(737 mm)
Depth	29.5"	(749 mm)
with handle	32.25"	(819 mm)
Weight	510 lbs.	(231 kg)
Cook Chamber		
Height	7.1"	(180 mm)
Width	17.8"	(452 mm)
Depth	14.5"	(368 mm)
Volume	1.06 cu. ft.	(30 liters)
Wall Clearance (Oven not intended for built-in installation)		
Top	4"	(102 mm)
Sides	2"	(51 mm)
ELECTRICAL SPECIFICATIONS		
NORTH AMERICA		
C3/C Single Model 50 HZ, 208 VAC (TC3-0602-1-208-1)		
C3/C Single Model 50 HZ, 240 VAC (TC3-0602-1-240-1)		
C3/C Single Model 60 HZ, 208 VAC (TC3-0602-1-208-2)		
C3/C Single Model 60 HZ, 240 VAC (TC3-0602-1-240-2)		
Phase	1 Phase	
Voltage	208 or 240 VAC	
Frequency	50 or 60 Hz	
Current	35/30 amp	
Cord	3 wire (inc. ground)	
Plug	NEMA 6-50P (35 amp)	
Max Input	7.4 kW	
Microwave Input Power	2 kW	
EUROPE/ASIA-PACIFIC		
C3/C Multi Model 50 Hz (TC3-0602-1W)		
C3/C Multi Model 60 Hz (TC3-0602-1W-2)		
Phase	3 Phase	
Voltage	380-415 VAC	
Frequency	50 or 60 Hz	

Current	12 amp	
Cord	5 Wire (inc. ground), 1.5m; H07RN-F	
Plug	IEC 309, 5 pin, 32 amp	
Max Input	7.4 kW	
Microwave Input Power	2 kW	
C3/C Multi Model 50 Hz (TC3-0602-1D)		
C3/C Multi Model 60 Hz (TC3-0602-1D-2)		
Phase	3 Phase	
Voltage	230 VAC	
Frequency	50 or 60 Hz	
Current	30 amp	
Cord	4 Wire (inc. ground)	
Plug	IEC 309, 4 pin, 32 amp	
Max Input	7.4 kW	
Microwave Input Power	2 kW	
C3/C Single Model 50 Hz (TC3-0602-1K)		
C3/C Single Model 60 Hz (TC3-0602-1K-2)		
Phase	1 Phase	
Voltage	230 VAC	
Freq	50 or 60 Hz	
Current	30 amp	
Cord	3 Wire (inc. ground), 1.5m, H07RN-F	
Plug	IEC 309, 3 pin, 32 amp	
Max Input	7.4 kW	
Microwave Input Power	2 kW	

SHIPPING INFORMATION

U.S.: All ovens shipped within the U.S. are packaged in a double-wall corrugated box banded to a wooden skid.

International: All International ovens shipped via Air or Less than Container Loads are packaged in wooden crates.

Box size: 37" x 32" x 32.5" (940mm x 813mm x 826mm)

Crate size: 39.5" x 34.5" x 34" (1003mm x 876mm x 864mm)

Item class: 85 NMFC #26770 HS code 8419.81

Approximate crated weight: 360 lbs. (163 kg)

Minimum entry clearance required for box: 32.5" (826mm)

Minimum entry clearance required for crate: 34" (864mm)

*All C3 multi-phase ovens can be field configured to allow single or 3 phase operation.

**TurboChef recommends installing a type D circuit breaker for all installations.

TurboChef reserves the right to make substitutions of components or change specifications without prior notice.

TurboChef Global Operations

4240 International Pkwy, Suite 105

Carrollton, Texas 75007 USA

US: 800.90TURBO (800.908.8726)

International: +1 214.379.6000

Fax: +1 214.379.6073

turbochef.com